

DIN 24154	Innen Ø	Tolerance Ø	Breite x Stärke	Lochkreis Ø	Loch*	Loch Ø	Gewicht
Reihe 3	Vnitřní Ø		Šířka x Síla	Roztečná kr. Ø	Počet děr	Otvor Ø	Váha
NW	di [mm]	[mm]	b x s [mm]	dk [mm]	z	d [mm]	[kg]
63	68	+1,0	20x4	92	4	7,0	0,17
71	76	+1,0	20x4	100	4	7,0	0,19
80	84	+1,0	20x4	108	4	7,0	0,21
90	94	+1,0	20x4	118	4	7,0	0,22
100	105	+1,0	20x4	129	4	7,0	0,25
112	117	+1,0	20x4	141	4	7,0	0,27
125	131	+1,0	20x4	155	4	7,0	0,30
140	146	+1,5	25x5	176	6	7,0	0,52
150	155	+1,5	25x5	185	6	7,0	0,55
160	164	+1,5	25x5	194	6	7,0	0,58
180	183	+1,5	25x5	213	6	7,0	0,64
200	205	+1,5	25x5	235	6	7,0	0,71
224	229	+1,5	25x5	259	6	7,0	0,78
250	256	+1,5	25x5	286	6	7,0	0,87
280	288	+1,5	30x6	322	8	9,5	1,41
300	305	+1,5	30x6	339	8	9,5	1,48
315	322	+1,5	30x6	356	8	9,5	1,56
350	355	+1,5	30x6	389	8	9,5	1,69
355	361	+1,5	30x6	395	8	9,5	1,73
400	404	+1,5	30x6	438	12	9,5	1,92
450	453	+1,5	30x6	487	12	9,5	2,12
500	507	+1,5	30x6	541	12	9,5	2,38
560	569	+2,0	35x6	605	16	11,5	3,13
600	605	+2,0	35x6	641	16	11,5	3,30
630	638	+2,0	35,60	674	16	11,5	3,48
710	715	+2,0	35x6	751	16	11,5	3,88
800	801	+2,0	35x6	837	24	11,5	4,33
900	902	+2,0	35x6	934	24	11,5	4,80
1000	1007	+2,0	35x6	1043	24	11,5	5,39
1120	1130	+2,0	40x8	1174	24	11,5	9,23
1250	1267	+2,0	40x8	1311	24	11,5	10,30
1400	1421	+2,0	40x8	1465	24	11,5	11,50
1600	1597	+2,0	40x8	1637	32	11,5	12,90
1800	1790	+2,0	40x8	1830	32	11,5	14,40
2000	2003	+2,0	40x8	2047	32	11,5	16,10

