

DIN 24154	Innen Ø	Tolerance Ø	Breite x Stärke	Lochkreis Ø	Loch*	Loch Ø	Gewicht
Reihe 5	Vnitřní Ø		Šířka x Síla	Roztečná kr. Ø	Počet děr	Otvor Ø	Váha
NW	di [mm]	[mm]	b x s [mm]	dk [mm]	z	d [mm]	[kg]
70	73	+1,0	25x3	100	4	7,0	0,18
80	85	+1,0	25x3	108	4	7,0	0,20
90	92	+1,0	25x3	118	4	7,0	0,21
100	105	+1,0	25x3	129	4	7,0	0,23
112	114	+1,0	25x3	141	4	7,0	0,25
125	130	+1,0	25x3	155	4	7,0	0,28
140	145	+1,5	30x4	176	6	9,5	0,50
150	154	+1,5	30x4	185	6	9,5	0,53
160	165	+1,5	30x4	194	6	9,5	0,56
180	184	+1,5	30x4	213	6	9,5	0,62
200	204	+1,5	30x4	235	6	9,5	0,69
224	229	+1,5	30x4	259	6	9,5	0,76
250	254	+1,5	30x4	286	6	9,5	0,83
280	284	+1,5	35x5	322	8	9,5	1,40
300	304	+1,5	35x5	342	8	9,5	1,48
315	319	+1,5	35x5	356	8	9,5	1,56
355	359	+1,5	35x5	395	8	9,5	1,73
400	404	+1,5	35x5	438	12	9,5	1,93
450	454	+1,5	35x5	487	12	9,5	2,15
500	504	+1,5	35x5	541	12	11,5	2,37
560	564	+2,0	45x6	629	16	11,5	4,00
600	606	+2,0	45x6	666	16	11,5	4,26
630	636	+2,0	45x6	698	16	11,5	4,47
710	716	+2,0	45x6	775	16	11,5	4,99
800	806	+2,0	45x6	861	24	11,5	5,55
900	906	+2,0	45x6	958	24	11,5	6,21
1000	1007	+2,0	45x6	1067	24	11,5	6,88
1120	1127	+2,0	55x8	1200	32	11,5	12,60
1250	1257	+2,0	55x8	1337	32	11,5	14,01
1400	1407	+2,0	55x8	1491	32	11,5	15,70
1600	1605	+2,0	55x8	1663	40	11,5	17,80
1800	1805	+2,0	55x8	1856	40	11,5	19,92
2000	2005	+2,0	55x8	2073	40	11,5	22,10

