

DIN 24155	Innen Ø	Tolerance Ø	Breite x Stärke	Lochkreis Ø	Loch*	Loch Ø	Gewicht
Winkel Reihe 3	Vnitřní Ø		Šířka x Síla	Roztečná kr. Ø	Počet děr	Otvor Ø	Váha
NW	di [mm]	[mm]	b x s [mm]	dk [mm]	z	d [mm]	[kg]
280	288	+1,5	30x30x5	322	8	9,5	2,18
315	322	+1,5	30x30x5	356	8	9,5	2,41
355	361	+1,5	30x30x5	395	8	9,5	2,68
400	404	+1,5	30x30x5	438	12	9,5	2,97
450	453	+1,5	30x30x5	487	12	9,5	3,31
500	507	+1,5	30x30x5	541	12	9,5	3,68
560	569	+2,0	35x35x5	605	16	11,5	4,87
630	638	+2,0	35x35x5	674	16	11,5	5,43
710	715	+2,0	35x35x5	751	16	11,5	6,05
800	801	+2,0	35x35x5	837	24	11,5	6,75
900	898	+2,0	35x35x5	934	24	11,5	7,53
1000	1007	+2,0	35x35x5	1043	24	11,5	8,41
1120	1130	+2,0	40x40x6	1174	24	11,5	12,90
1250	1267	+2,0	40x40x6	1311	24	11,5	14,40
1400	1421	+2,0	40x40x6	1465	24	11,5	16,10
1600	1593	+2,0	40x40x6	1637	32	11,5	18,00
1800	1786	+2,0	40x40x6	1830	32	11,5	20,10
2000	2003	+2,0	40x40x6	2047	32	11,5	22,50

